
Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Bow shackle - Dia 16 mm

Part #1247





Description

Bow shackle forged in grade 316L stainless steel
No risks of loose due to vibrations
Outstanding working and breaking loads
WLL: only for industrial applications (lifting i.e...)
CE marking
Part # 1247 is not self-locking

Applications

To be used when ample room is required
Possibility to attach several lines or cables

Technical information

	Materials	316 stainless steel grade
	Working load (kg)	3200
	WLL (kg)	2000
	Breaking load (kg)	10000
	Weight (g)	540
	A (mm)	70
	B (mm)	32
	C (mm)	16
	D (mm)	32
	D diameter (mm)	16
	E (mm)	15
	F (mm)	112
	G (mm)	88
	H (mm)	51
	M (mm)	85

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026