
Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Captive pin twisted shackle - Dia 8 mm

Part #1424





Description

Captive pin twisted shackle forged in grade 316L stainless steel
The pin is connected to the body at all times even when opened
The pin is locked into one of the indentations
No risks of loose due to vibrations
Outstanding working and breaking loads
Single handed operation for more safety
The part # 1424 is not suitable for lifting applications

Applications

Perfect for application where a 90° angle twist setup is required
Often used to attach an unarticulated part (block on a rail) or on purchases

Technical information

	Materials	316 stainless steel grade
	Working load (kg)	1000
	Breaking load (kg)	3700
	Weight (g)	90
	A (mm)	59
	B (mm)	16
	C (mm)	9
	D (mm)	18
	D diameter (mm)	8
	E (mm)	8
	F (mm)	80
	G (mm)	42

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026