Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Double fairlead - For 25 mm dia stanchion - With webbing

Part #20220



Description

Quick and easy installation and dismantling:
Thanks to the velcro stripe, the double fairlead can be installed easily and quickly on 25 mm
stanchion. It enables a quick installation and use of the continuous line of your flying sails furler
or spinnaker furler. The dismantling is as easy and enables to store the whole set (fairlead and continuous line).
In case the continuous line is already spliced, the fairlead can be opened to install the line.
This double fairlead has no moving parts and thus offers a greater lifespan and minimal maintenance.

Applications

Use of the continuous line of your flying sails furler or spinnaker furle

Technical information

Materials	316L stainless steel grade
Weight (g)	180

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026