
Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

HR snap shackle - With swivel eye - Length: 70 mm

Part #2473





Description

HR Forged snap shackle (Grade 17.4 ph stainless steel) with swivel eye
Free rotation of the snap shackle thanks to the swivel eye
The plunger pin is set captive into the hook and cannot become detached
Excellent working and breaking loads
Easy to open by pulling the plunger pin (possiblity to attach a lanyard)

Applications

Snap shackle applications
Applications requiring a free rotation of the snap shackle (for a better sail orientation)

Technical information

	Materials	HR 17.4 PH stainless steel grade
	Length (mm)	70
	Working load (kg)	960
	Breaking load (kg)	2000
	Weight (g)	65
	A (mm)	16
	B (mm)	11

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026