
Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Double folding pad eye - Dia 10 mm

Part #6566





Description

Fully dropforged product with outstanding working and breaking loads regardless the angle of the load
Perfect solution attachment (stay, blocks, jib tack point)
Possibility to attach several stays
Modern and optimized design to suit aesthetics of modern boats
They can be fold down to minimize the risk of injuries
The silicon pad eliminates moise and unpleasant vibrations

Applications

For any fastening/attachment application
Allows to attach several shrouds

Technical information

	Materials	316L stainless steel grade
⛵	Working load (kg)	4560
	Breaking load (kg)	9000
	Weight (g)	494
	A (mm)	75
	B (mm)	45
	C (mm)	23
	d diameter (mm)	10.5
	D diameter (mm)	10
	E (mm)	104
	F (mm)	78

Caption

⛵ Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026