Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Double ball bearing block - Sheave 18 - Fixed eye & becket

Part #70214



Description

Gamme complète de poulies à billes au design moderne
Concept novateur avec deux rangées de billes latérales
Excellent rendement sous faible charge (en cas d'embraquage rapide)
Sous forte charge, les efforts sont repris par l'axe en inox sans ecrasement des billes et de frictions latérales.
Protection du réa par les flasques
Réa démontable pour l'entretien
Large choix de fixations grâce à la tête universelle

Applications

Pour voile légère: écoute de foc , hale-bas de bôme, cunningham, rail d'écoute de grand-voile
Pour croiseurs: barber-hauler, divers réglages,

Technical information

Materials	Grade 316L stainless steel head Delrin® ball bearings configuration Grade 316L stainless steel load straps Polycarbonate cheeks Composite sheave
Rope size	Pour cordage de 4 à 6 mm
Length (mm)	55
Width (mm)	18
Thickness (mm)	28
Sheave diameter (mm)	18
Working load (kg)	320
Breaking load (kg)	700
Weight (g)	44

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2026